

# FRESH WATER PUMPS

## PENTAIR SHURFLO® AQUA KING® II FRESH WATER PUMPS 2.0 GPM & 3.0 GPM



CE

Name	OEM Model # (Aftermarket)	Description	Voltage	Dimensions	Flow Rate	Amps (Max.)	Shut-Off Pressure
Shurflo Aqua King II Junior 2.0	4128-110-A04 (4128-110-E04)	Intermittent Duty Up to 2 Fixtures	12 VDC	8.2" x 4.9" x 4.1" [208 x 124 x 104mm]	2.0 GPM [7.6 LPM]	3.5	30 PSI [2.0 BAR]
Shurflo Aqua King II Standard 3.0	4138-111-A65 (4138-111-E65)	Intermittent Duty Multi-Fixture Application	12 VDC	8.2" x 4.9" x 4.1" [208 x 124 x 104mm]	3.0 GPM [11.35 LPM]	6.5	55 PSI [3.8 BAR]
Shurflo Aqua King II Standard 3.0	4138-131-A65 (4138-131-E65)	Intermittent Duty Multi-Fixture Application	24 VDC	8.2" x 4.9" x 4.1" [208 x 124 x 104mm]	3.0 GPM [11.35 LPM]	3.8	55 PSI [3.8 BAR]

Pentair Shurflo Aqua King II Junior and Standard Fresh Water Pumps are designed with unique over-molded single piece diaphragm and internal bypass (3.0 version only) to enable long life and top performance in all plumbing systems. These fresh water automatic demand pumps are quiet and can run dry without damage. Sealed switch. Ignition protected. Thermally protected. 2 each 1/2" hose barb fittings are included (aftermarket models only).

**3 Year Warranty**

## PENTAIR SHURFLO AQUA KING II FRESH WATER PUMPS 4.0



CE

Name	OEM Model # (Aftermarket)	Description	Voltage	Dimensions	Flow Rate	Amps (Max.)	Shut-Off Pressure
Shurflo Aqua King II Premium 4.0	4148-153-A75 (4148-153-E75)	Intermittent Duty Multi-Fixture Application	12 VDC	10" x 5" x 4.75" [254 x 127 x 120mm]	4.0 GPM [15.1 LPM]	10	55 PSI [3.8 BAR]
Shurflo Aqua King II Premium 4.0	4148-163-A75 (4148-163-E75)	Intermittent Duty Multi-Fixture Application	24 VDC	10" x 5" x 4.75" [254 x 127 x 120mm]	4.0 GPM [15.1 LPM]	5	55 PSI [3.8 BAR]

Pentair Shurflo Aqua King II Premium Fresh Water Pumps are designed for boats with multi-fixtures providing "just like home" shower pressure. A built-in mechanical bypass function enables these pumps to operate at lower flow conditions with minimal cycling. Featuring heavy duty, seamless shell electro coated motors built to withstand the tough marine environment with o-ring sealed end bells and completely sealed wire entries. Sealed switch. Ignition protected. Thermally protected. Inlet strainer and 2 each 1/2" hose barb fittings are included (aftermarket models only).

**3 Year Warranty**

## PENTAIR SHURFLO AQUA KING II FRESH WATER PUMPS 5.0



CE

Name	OEM Model # (Aftermarket)	Description	Voltage	Dimensions	Flow Rate	Amps (Max.)	Shut-Off Pressure
Shurflo Aqua King II Supreme 5.0	4158-153-A75 (4158-153-E75)	Intermittent Duty Multi-Fixture Application	12 VDC	10" x 5" x 4.75" [254 x 127 x 120mm]	5.0 GPM [18.9 LPM]	13	55 PSI [3.8 BAR]
Shurflo Aqua King II Supreme 5.0	4158-163-A75 (4158-163-E75)	Intermittent Duty Multi-Fixture Application	24 VDC	10" x 5" x 4.75" [254 x 127 x 120mm]	5.0 GPM [18.9 LPM]	7	55 PSI [3.8 BAR]

Pentair Shurflo Aqua King II Supreme Fresh Water Pumps are designed for boats with multi-fixtures providing "just like home" shower pressure. A built-in mechanical bypass function enables these pumps to operate at lower flow conditions with minimal cycling. Featuring heavy duty, seamless shell electro coated motors built to withstand the tough marine environment with o-ring sealed end bells and completely sealed wire entries. Sealed switch. Ignition protected. Thermally protected. Inlet strainer and 2 each 1/2" hose barb fittings are included (aftermarket models only).

**3 Year Warranty**