WASHDOWN PUMPS



PENTAIR SHURFLO* BLASTER II WASHDOWN KIT

| Name | 0EM Model # (Aftermarket) | Description | Dimension | Voltage | Flow Rate | Amps (Max.) | Shut-Off Pressure |
|--|--------------------------------|---|---|---------|-----------------------|----------------|----------------------|
| Shurflo Blaster II Washdown Kit 3.5 GPM | 4338-121-A07 (4338-121-E07) | PentairShurflo Blaster II 3.5 Pump, Fittings, Nozzle, Strainer, 25' 3/8" coiled hose | 9" x 4.9" x 4.1" [229 x 124 x 104mm] | 12 VDC | 3.5 GPM [13.2 LPM] | 7.5 | 45 PSI [3.1 BAR] |

Pentair Shurflo Blaster II Washdown Kit includes everything you need for washdown applications in fish box, scaling, anchor chain cleaning and blasting down the grimiest decks all in one convenient package. The kit includes the Pentair Shurflo Blaster II 3.5 GPM pump, nozzle, strainer, fittings and a UV protected 25' coiled hose.

2 Year Warranty



PENTAIR SHURFLO PRO WASHDOWN KIT II

| Name | OEM Model # (Aftermarket) | Description | Dimension | Voltage | Flow Rate | Amps (Max.) | Shut-Off Pressure |
|--|--------------------------------|--|--|---------|-----------------------|----------------|----------------------|
| Shurflo Pro Washdown Kit II Deluxe 4.0 (A) | 4348-153-A09 (4348-153-E09) | Pentair Shurflo Pro Blaster II Deluxe 4.0 Pump, Fittings, Nozzle, Raw Water Strainer, 25' 3/8" coiled hose | 10" x 5" x 4.75" [254 x 127 x 120mm] | 12 VDC | 4.0 GPM [15.1 LPM] | 10 | 60 PSI [4.1 BAR] |
| Shurflo Pro Washdown Kit II Ultimate 5.0 | 4358-153-A09 (4358-153-E09) | Pentair Shurflo Pro Blaster II Ultimate, 5.0 Pump, Fittings, Nozzle, Raw Water Strainer, 25' 1/2" coiled hose | 10" x 5" x 4.75" [254 x 127 x 120mm] | 12 VDC | 5.0 GPM [18.9 LPM] | 14 | 60 PSI [4.1 BAR] |

Pentair Shurflo Pro Washdown Kit II is available in both Deluxe 4.0 and Ultimate 5.0 series. These kits include everything you need for those tough washdown applications in fish box, scaling, anchor chain cleaning and blasting down the grimiest decks all in one kit! The kits include a washdown pump (Deluxe 4.0 or Ultimate 5.0), fittings, nozzle, raw water strainer and a 25' coiled hose.